TASK SHEET NATEF STANDARD A.5 D.1,7,8 (P-1)

A5D8: REMOVE AND INSTALL FRONT BRAKE ROTOR

Student:		Date:	Period:				
VIN:	Year:	Make:	Model:				
Engine:	Transmission:	Productio	on Date:				
Objective:	Student will remove and install the front brake rotor, evaluate overall condition, and determine necessary action.						
<u>Materials:</u>	 EYE PROTECTION Floor Jack and Safety Hand Tools and Lug Micrometer and Dial Vehicle (see instructor) 	V Stands or Hoist Wrench Indicator					
<u>Procedures</u>	raise vehicle with floor jack a Lower vehicle and determine and brake pads. Measure late specifications. See "All-Data installation instructions and s Remove cotter pin and wheel bearing. FWD: Remove from	and place safety sta e if secure. Remove ral runout and reco a" or equivalent prin specifications. RWI bearing retaining n t rotor. Measure rot	nt out disc/rotor removal and D: Remove front hub dust cap.				

Compare to specifications. Re-install rotor on vehicle being sure not to get grease, dirt, or finger prints on rotor face. Install caliper and brake pads. Torque mounting bolts. <u>Record MOUNTING BOLT TORQUE</u>_____FTLBS.

Install wheel and torque lug nuts to specs. <u>LUG NUT TORQUE</u>_____FTLBS.

	MEASURED / OBSERVED	SPECIFICATIONS
ROTOR THICKNESS (INCHES)		MIN. THICKNESS
LATERAL RUNOUT (INCHES)		MAX. RUNOUT
SURFACE CONDITION		SMOOTH SHINY SILVER SURFACE

IF THE LATERAL RUNOUT SPECIFICATION IS EXCEEDED, WHAT COMPLAINT WOULD YOU EXPECT TO HEAR FROM THE VEHICLE OWNER?

YOUR RECOMMENDATIONS:

(Does it need to be replaced? Why?)

LEVEL OF SKILL ATTAINED	Initial	OVERALL SKILL EVALUATION		Points	
DEMONSTRATES MASTERY (5)			DOCUMENTATION COMPLETENESS (1)		
PERFORMS SATISFACTORILY (4)			SAFETY COMPLIANCE (1)		
CAPABLE, NEEDS PRACTICE (3)		N	Work Professionalism (3)		
Assisted in Performing (2)			LEVEL OF SKILL ATTAINED (1-5)		
EXPOSURE, OBSERVATION (1)] '	TOTAL SCORE		
INSTRUCTOR'S SIGNATURE:	•	•			

A5D8 R&I Rotor / 10-10-10 / vdb